

Super Shed Felt

Product Data Sheet

Extra Durable Felt for Sheds and Garden Buildings

August 2012

Features and Benefits

- Advanced formula roofing felt
- High performance waterproofing
- Installed in exactly the same way as traditional shed felt
- Longer life expectancy (up to 15 years)
- Peace of mind protection from the elements
- Ideal for garden buildings that house possessions important to you

Description

IKO Super Shed felt is a longer lasting, polyester reinforced felt, with a green mineral finish. Available in 1m x 8m rolls, this robust waterproofing membrane is expected to last up to 15 years.

Product Details

| | Super Shed Felt |
|------------------|-----------------|
| Roll Weight (kg) | 17kg |
| Roll Dimensions | 8m x 1m |
| Base Type | Polyester |

Typical Properties

| Property | Test Method | Unit | Super Shed Felt | |
|----------------------|-----------------|--------|-----------------|------|
| Tensile Strength | BSEN 12311-2000 | N/50mm | MD | >300 |
| | | | TD | >200 |
| Elongation at Break | BSEN 12311-2000 | % | MD | >30 |
| | | | TD | >40 |
| Nail Tear Resistance | BSEN 12311-2000 | N/50mm | MD | >120 |
| | | | TD | >130 |

Application

Used as a single, two-layer or three-layer application, Super Shed Felt is ideal for use on sheds and other garden buildings.

Super Shed Felt should be installed in accordance with the relevant sections of BS 8217: 2005, Code of practice for reinforced bitumen membranes for roofing and to IKO's specifications.

If applied by traditional pour and roll methods, hot bitumen is poured (or applied by a mop) in front of the roofing felt roll, which is then unrolled into the bitumen, spreading it to give a continuous coating for the full width. The membrane is applied with minimum 75 mm side and end laps.

Where used as a single layer on a shed roof, the minimum pitch of the roof should be 20 degrees. Super Shed Felt should be nail fixed with the laps fully sealed in IKOpro HP Cold Adhesive.



Other Products

Full product literature, health & safety and technical sheets are available as downloads from our website: www.ikogroup.co.uk or on request by email: marketing@ikogroup.co.uk

IKO PLC

Literature Enquiries

Tel: 0844 412 8554

E-Mail: marketing@ikogroup.co.uk Website: www.ikogroup.co.uk

Customer Services

Appley Lane North, Appley Bridge, Wigan, Lancashire WN6 9AB Tel: 0844 873 1062 Fax: 0844 873 1067 E-Mail: sales@ikogroup.co.uk

Technical & Design Services

Appley Lane North, Appley Bridge, Wigan, Lancashire WN6 9AB

Tel: 0844 412 8551 Fax: 0844 412 7229 E-Mail: technical@ikogroup.co.uk



Whilst every care is taken to see that the information given in this literature is correct and up to date it is not intended to form part of any contract or give rise to any collateral liability, which is hereby specifically excluded. Intending purchasers of our materials should therefore verify with the company whether any changes in our specification or application details or otherwise have taken place since this literature was issued.

Company Registered in England No. 2678296 - Registered Office: Appley Lane North, Appley Bridge, Wigan, Lancashire, WN6 9AB

